

# Horizontal Blind Installation Instructions


## Tools you may need

Measuring Tape  
Level  
1/4" Magnetic Nut Driver  
Cordless Drill  
Screwdriver  
Ladder/Step Stool



## Hardware you will receive

Installation Brackets  
Mounting Screws  
Valance Clips  
Small Screws




## Contents may include the following


3/8" Spacer Block  
Support Bracket  
Metal Extension Bracket  
Valance Return Brackets & Corner Inserts  
Hold Down Brackets  
Cord Cleat

## Installation

Hold the Installation bracket in place. Set brackets to proper depth in the window sill and install the brackets. (Valance type will determine the depth of the bracket) Insert the screws into the 1/4" magnetic nut driver / screw driver and mount brackets to the wall.





Keeping bracket flap in "OPEN position", insert the headrail into the bracket by sliding it in the open face of bracket. Close the flap to lock the blind securely into place.



## Valance installation



### With Valance Returns

Locate groove on back of valance. Place clip sideways in groove and turn clip to lock into correct position. Place rounded clips on the front edge of the headrail. Once clips are in headrail, slightly pull valance downward




### Without Valance Returns

Separate the two parts of the valance clips. Attach the pieces with the top rounded clip spaced out across the headrail. Insert the back of the other pieces into the groove on the back of the valance and twist to lock into place. Make sure the pieces attached to the valance line up with the pieces attached to the headrail. Push the clips on the valance into the clips attached to the headrail.



## Attaching valance returns If needed

Place valance return insert into slot in back of return. Then slide insert with the attached return into adjoining slot on the back of the valance.



## Operating your new blinds

Each cord with individual tassels will tilt the slats in alternate directions.

The lift cord is used to raise and lower the blinds. Pull the cord away from the window to lift the blind and lock in position. Pull toward the center to release the blind from the locked position.

The slats must be open when raising or lowering the blind.

## Care and cleaning of your blinds

Tilt slats almost all the way in one direction. Dust may be easily brushed off using a feather duster. Turn the slats in the other direction and repeat. Never immerse your blinds in water.

